



# Hearing protection ZEKLER 412RD

Comfortable earmuffs with built-in stereo FM radio and level-dependent monitoring function. The microphones on the cups' front take in the ambient sound so that you can hear what's happening around you and facilitate communication with your workmates. If the noise comes up to dangerous levels the electronics react straight away and reduce the level to max 82 dB(A). A great aid in environments with impulse noise or varying noise levels. You choose the mix of functions you want (radio or level-dependent monitoring) which is most practical at any moment. Fitted with a 3.5 mm aux audio input channel for connecting an MP3 player, for example.Excellent noise reduction over low. medium and high frequencies. The headband fitting has a fork-mount and the wide sealing cushions make for an even head pressure and comfort.

- Attenuation level: Level 2.
- Stereo FM Radio 88 108 MHz with noise level limiter (82dB(A)).
- Level-dependent monitoring function, Level Dependent System.
- 3.5 mm AUX input.
- Cable with 2x3.5 mm stereo plugs included.
- 2 x 1.5V AA batteries operation time around 120 hours.
- Adjustable head fitting.
- Soft, replaceable headband cushion.
- Wide, comfortable and easily replaced sealing cushions.

Complies with EN 352-1, 352-4, 352-6, 352-8



Frequency Hz	63	125	250	500	1000	2000	4000	8000
Median value (dB)	21	18,4	21,1	27,7	36,9	36,1	42,1	38,8
Standard deviation (dB)	6,3	4,5	4,2	3,5	4	3,6	3,5	5,4
Anticipated attentuation (dB)	14,7	13,9	16,9	24,2	32,9	32,5	38,6	33,4

 H
 M
 L
 SNR

 34
 27
 20
 30

Code	Description	Туре	Colour	Unit	Pack
380682005	Hearing protection	412RD	Black	PAC	1
380684027	Hygiene kit	НКЗ		PAC	1
380684035	Comfort ring	CR1			1
380684043	Cable 3,5 mm x 2				1
380684092	Windshield for monitoring microphone				1





# Hearing protection ZEKLER 412RDH

Comfortable earmuffs with built-in stereo FM radio and level-dependent monitoring function. The microphones on the cups' front take in the ambient sound so that you can hear what's happening around you and facilitate communication with your workmates. If the noise comes up to dangerous levels the electronics react straight away and reduce the level to max 82 dB(A). A great aid in environments with impulse noise or varying noise levels. You choose the mix of functions you want (radio or level-dependent monitoring) which is most practical at any moment. Fitted with a 3.5 mm aux audio input channel for connecting an MP3 player, for example. Excellent noise reduction over low. medium and high frequencies. The headband fitting has a fork-mount and the wide sealing cushions make for an even head pressure and comfort.

- Attenuation level: Level 2.
- Stereo FM Radio 88 108 MHz with noise level limiter (82dB(A)).
- Level-dependent monitoring function, Level Dependent System.
- 3.5 mm AUX input.
- Cable with 2x3.5 mm stereo plugs included.
- 2 x 1.5V AA batteries operation time around 120 hours.
- Adjustable head fitting.
- For hard hat attachment.
- Soft, replaceable headband cushion.
- Wide, comfortable and easily replaced sealing cushions.

Approved for mounting on the following protective helmets: IRIS 2, Style 300, Style 600, Balance AC, Balance HD, Peltor G2000 and Peltor G3000. Complies with EN 352-3, 352-4, 352-6, 352-8



Frequency Hz		63	125	250	500	1000	2000	4000	8000
Median value (c	IB)	17,8	16,3	19,5	26,9	34,3	33,8	41,8	37,4
Standard deviat	ion (dB)	4,2	4	3,2	3,1	4	2,9	3,3	3,8
Anticipated atte	enuation (dB)	13,6	12,3	16,3	23,8	30,3	30,9	38,5	33,6
Code	Description					Туре	Colou	r Unit	Pack
380682013	Hearing protection					412RDH	Black	PAC	1
380684027	Hygiene kit					НКЗ		PAC	1
380684035	Comfort ring					CR1			1
380684043	Cable 3,5 mm x 2								
380684092	Windshield for monitorin	g microp	hone						

Marketed by Skydda, Northern Europe's leading concept with Personal Protection Equipment www.skydda.com





# Hearing protection ZEKLER 412R

Comfortable earmuffs with built-in stereo FM radio. Enables the user to listen to the radio instead of noise, without disturbing anyone else. Increases comfort and at the same time increases hearing protection use. Fitted with 3.5 mm aux audio inputs for connecting an MP3 player, for example. Good attentuation at mid, high and low frequencies. Headband fitting with fork mount and the wide sealing cushions provide an even head pressure and make for comfotable use.

- Attenuation level: Level 2.
- Stereo FM Radio 88 108 mhz with noise level limiter (82dB(A)).
- 3.5 mm AUX input.
- Cables 2x3.5 mm stereo plugs included.
- 2 x 1.5V AA batteries operational time around 130 hours.
- Adjustable head fitting.
- Soft replacable head cushion.
- Wide, comfortable and easily replaced sealing cushions.

#### Complies with EN 352-1, 352-6, 352-8

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Median value (dB)	21	18,4	21,1	27,7	36,9	36,1	42,1	38,8
Standard deviation (dB)	6,3	4,5	4,2	3,5	4	3,6	3,5	5,4
Anticipated attenuatuion (dB)	14,7	13,9	16,9	24,2	32,9	32,5	38,6	33,4

H M L SNR 34 27 20 30

Code	Description	Туре	Colour	Unit	Pack
380682021	Hearing protection	412R	Black	PAC	1
380684027	Hygiene kit	НКЗ		PAC	1
380684035	Comfort ring	CR1			1
380684043	Cable 3,5 mm x 2				





# Hearing protection ZEKLER 412RH

Comfortable earmuffs with built-in stereo FM radio. Enables the user to listen to the radio instead of noise, without disturbing anyone else. Increases comfort and at the same time increases hearing protection use. Fitted with 3.5 mm aux audio inputs for connecting an MP3 player, for example. Good attentuation at mid, high and low frequencies. Headband fitting with fork mount and the wide sealing cushions provide an even head pressure and make for comfotable use.

- Attenuation level: Level 2.
- Stereo FM Radio 88 108 mhz with noise level limiter (82dB(A)).
- 3.5 mm AUX input.
- Cables 2x3.5 mm stereo plugs included.
- 2 x 1.5V AA batteries operational time around 130 hours.
- Adjustable head fitting.
- For hard hat attachment.
- Soft replacable head cushion.
- Wide, comfortable and easily replaced sealing cushions.

Approved for mounting on the following safety helmets: IRIS 2, Style 300, Style 600, Balance AC, Balance HD, Peltor G2000 och Peltor G3000 Complies with EN 352-3, 352-6, 352-8



Frequency Hz	63	125	250	500	1000	2000	4000	8000
Median value (dB)	17,8	16,3	19,5	26,9	34,3	33,8	41,8	37,4
Standard deviation (dB)	4,2	4	3,2	3,1	4	2,9	3,3	3,8
Anticipated attenuation (dB)	13,6	12,3	16,3	23,8	30,3	30,9	38,5	33,6

HMLSNR33261929

Code	Description	Туре	Colour	Unit	Pack
380682039	Hearing protection	412RH	Black	PC	1
380684027	Hygiene kit	НК3		KIT	1
380684035	Comfort ring	CR1		BAG	1
380684043	Cable 3,5 mm x 2				





## Hearing protection ZEKLER 412D

Comfortable earmuffs with level-dependent monitoring function. The microphones on the cups' front take in the ambient sound so that you can hear what's happening around you and facilitate communication with your workmates. If the noise comes up to dangerous levels the electronics react straight away and reduce the level to max 82 dB(A). A great aid in environments with impulse noise or varying noise levels. Fitted with a 3.5 mm aux audio input channel for connecting an MP3 player, for example. Good noise reduction over low. medium and high frequencies. The headband fitting has a fork-mount and the wide sealing cushions make for an even head pressure and comfort.

- Attenuation level: Level 2.
- Level-dependent monitoring function, Level Dependent System.
- 3.5 mm AUX input.
- Cable with 2x3.5 mm stereo plugs included.
- 2 x 1.5V AA batteries operation time around 120 hours.
- Adjustable head fitting.
- Soft, replaceable head cushion.
- Wide, comfortable and easily replaced sealing cushions.

#### Complies with EN 352-1, 352-4, 352-6

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Median value (dB)	21	18,4	21,1	27,7	36,9	36,1	42,1	38,8
Standard deviation (dB)	6,3	4,5	4,2	3,5	4	3,6	3,5	5,4
Anticipated attenuation (dB)	14,7	13,9	16,9	24,2	32,9	32,5	38,6	33,4

#### H M L SNR 34 27 20 30

Code	Description	Туре	Colour	Unit	Pack
380682047	Hearing protection	412D	Black	PC	1
380684027	Hygiene kit	НКЗ		KIT	1
380684035	Comfort ring	CR1		BAG	1
380684043	Cable 3,5 mm x 2				
380684092	Wind shield for monitoring microphone				





# Hearing protection ZEKLER 412DH

Comfortable earmuffs with built-in stereo FM radio and level-dependent monitoring function. The microphones on the cups' front take in the ambient sound so that you can hear what's happening around you and facilitate communication with your workmates. If the noise comes up to dangerous levels the electronics react straight away and reduce the level to max 82 dB(A). A great aid in environments with impulse noise or varying noise levels. Fitted with a 3.5 mm aux audio input channel for connecting an MP3 player, for example. Good noise reduction over low. medium and high frequencies. The headband fitting has a fork-mount and the wide sealing cushions make for an even head pressure and comfort.

- Attenuation level: Level 2.
- Level-dependent monitoring function, Level Dependent System.
- 3.5 mm AUX input.
- Cable with 2x3.5 mm stereo plugs included.
- 2 x 1.5V AA batteries operation time around 120 hours.
- Adjustable head fitting.
- For hard hat attachment.
- Soft, replaceable head cushion.
- Wide, comfortable and easily replaced sealing cushions.

Approved for mounting on the following safety helmets: IRIS 2, Style 300, Style 600, Balance AC, Balance HD, Peltor G2000 och Peltor G3000 Complies with EN 352-3, 352-4, 352-6



Frequency Hz	63	125	250	500	1000	2000	4000	8000
Median vlaue (dB)	17,8	16,3	19,5	26,9	34,3	33,8	41,8	37,4
Standard deviation (dB)	4,2	4	3,2	3,1	4	2,9	3,3	3,8
Anticipated attenuation (dB)	13,6	12,3	16,3	23,8	30,3	30,9	38,5	33,6

 H
 M
 L
 SNR

 33
 26
 19
 29

Code	Description	Туре	Colour	Unit	Pack
380682054	Hearing protection	412DH	Black	PC	1
380684027	Hygiene kit	НКЗ		KIT	1
380684035	Comfort ring	CR!		BAG	1
380684043	Cable 3,5 mm x 2				
380684092	Wind shield for monitoring microphone				

Marketed by Skydda, Northern Europe's leading concept with Personal Protection Equipment www.skydda.com





# Hearing protection ZEKLER 401

Comfortable earmuffs with headband fitting. Particularly good attenuation across medium and high frequencies. Headband fitting with fork-mount and the wide sealing cushions for comfortable use. Especially suited in lower ambient noise level environments.

- Attenuation level: Level 1
- Adjustable headband fitting.
- Soft, replacable headband cushion.
- Wide, cocmfortable and easily replaced sealing cushions.

## Complies with EN 352-1

Frequency HZ	63	125	250	500	1000	2000	4000	8000
Median value (dB)	13,8	10,9	15,6	25,4	31,1	30,8	33,8	33,5
Standard deviation (dB)	4,7	2,3	2,2	3,4	3,0	2,3	3,1	2,6
Anticipated attenuation (dB)	9,1	8,6	13,4	22,0	28,1	28,5	30,7	30,9

Н	М	L	SNR
30	23	15	26

Code	Description	Туре	Colour	Unit	Pack
380682062	Hearing protection	401	Black	PC	1
380684001	Hygiene kit	HK1		KIT	1
380684035	Comfort ring	CR1		BAG	1







# Hearing protection ZEKLER 401H

Comfortable earnuffs with hard hat attachment. Particularly good attenuation across medium and high frequencies. The hard hat attachment with fork-mount and the wide sealing cushions give a constant head presure and comfortable use. Especially suited in lower ambient noise level environments. Helmet adapter prepared for mounting the Zekler visor system.

- Attenuation level: Level 1
- For hard hat attachment.
- Helmet adapter prepared for mounting the Zekler visor system.
- Wide, cocmfortable and easily replaced sealing cushions.

Approved for mounting on the following safety helmets: IRIS 2, Style 300, Style 600, Balance AC, Balance HD, Peltor G2000, Peltor G3000, Uvex Airwing, Uvex Pheos, Uvex Pheos Alpine, JSP EVO2, EVO3, MK7 and LAS Rockman S14, S16 och S17.

#### Complies with EN 352-3

Frequ	uency H	Z			63	125	250	500	1000	2000	4000	8000
Medi	an value	: (dB)			15,0	15,0	14,7	24,7	33,1	26,8	32,2	34,6
Stand	dard dev	iation (d	B)		4,2	3,1	2,9	2,9	3,2	2,7	2,8	3,7
Antic	ipated a	ttenuati	on (dB)		10,8	11,9	11,8	21,8	29,9	24,1	29,4	30,9
Н	М	L	SNR									
24	23	16	25									
Cod	е		Desci	iption			٦	Гуре	Colo	ur	Unit	Pack
380	582070		Hearir	g protectior	า		4	01H	Blac	k	PC	1
380	584001		Hygier	ne kit			ŀ	HK1			KIT	1
380	684035		Comfo	ort ring			(	CR1			BAG	1







# Hearing protection ZEKLER 401N

Comfortable earmuffs with neckband. Particularly good attenuation across medium and high frequencies. Neckband in plastic-covered stainless steel and the wide sealing cushions give a constant head pressure and comfortable use. Especially suited in lower ambient noise level environments.

- Attenuation level: Level 1
- Neckband in plastic-covered stainless.
- Soft, easy to adjust overhead fitting.
- Wide, cocmfortable and easily replaced sealing cushions.

#### Complies with EN 352-1

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Median value (dB)	12,6	11,7	15,9	22,5	30,5	31,2	34,5	33,8
Standard deviation (dB)	4,1	2,7	1,9	2,7	2,8	3,5	3,2	4,7
Anticipated attenuation (dB)	8,5	9,0	14,0	19,8	27,7	27,7	31,3	29,1

H M L SNR 29 23 16 26

Code	Description	Туре	Colour	Unit	Pack
380682088	Hearing protection	401N	Black	PC	1
380684001	Hygiene kit	HK1		KIT	1
380684035	Comfort ring	CR1		BAG	1







# Hearing protection ZEKLER 402

Comfortable earmuffs with headband fitting for more demanding noisy environments. Good attenuation across medium, high and low frequencies. Headband fitting with forkmount and the wide side sealing custions make for an even head pressure and comfort.

- Attenuation level: Level 2
- Adjustable headband fitting.
- Soft, replacable headband cushion.
- Wide, comfortable and easily replaced sealing cushions.

#### Complies with EN 352-1

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Median value (dB)	18,2	13,6	21,8	30,7	39,4	35,8	37,6	40,0
Standard deviation (dB)	5,4	3,4	2,7	3,1	3,0	2,9	2,8	4,8
Anticipated attenuation (dB)	12,8	10,2	19,1	27,6	36,4	32,9	34,8	35,2

H M L SNR 35 28 18 30

Code	Description	Туре	Colour	Unit	Pack
380682096	Hearing protection	402	Black	PC	1
380684019	Hygiene kit	HK2		KIT	1
380684035	Comfort ring	CR1		BAG	1







## Hearing protection ZEKLER 402H

Comfortable earnuffs with hard hat attachment for more demanding noisy enviroments. Good attenuation across medium, high and low frequencies. The hard hat attachment with fork-mount and the wide sealing cushions give a constant head presure and comfortable use. Helmet adapter prepared for mounting the Zekler visor system.

- Attenuation level: Level 2
- For hard hat attachment.
- Helmet adapter prepared for mounting the Zekler visor system.
- Wide, cocmfortable and easily replaced sealing cushions.

Approved for mounting on the following safety helmets: IRIS 2, Style 300, Style 600, Balance AC, Balance HD, Peltor G2000, Peltor G3000, Uvex Airwing, Uvex Pheos, Uvex Pheos Alpine, JSP EVO2, EVO3, MK7 and LAS Rockman S14, S16 och S17.

#### Complies with EN 352-3

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Median value (dB)	15,0	15,0	21,0	28,1	35,3	34,0	34,0	37,3
Standard deviation (dB)	4,1	2,6	3,1	3,5	4,0	3,8	4,5	4,4
Anticipated attenuation (dB)	10,9	12,4	17,9	24,6	31,3	30,2	29,5	32,9

H M L SNR 31 27 19 29

Code	Description	Туре	Colour	Unit	Pack
380682104	Hearing protection	402H	Black	PC	1
380684019	Hygiene kit	HK2		KIT	1
380684035	Comfort ring	CR1		BAG	1







# Hearing protection ZEKLER 402N

Comfortable earmuffs with neckband for more demanding noisy environments. Good attenuation across medium, high and low frequencies. Neckband in plastic-covered stainless steel and the wide sealing cushions give a constant head pressure and comfortable use. For use together with other types of protection such as visor, welding helmet or safety helmet.

- Attenuation level: Level 2
- Neckband in plastic-covered stainless.
- Soft, easy to adjust overhead fitting.
- Wide, comfortable and easily replaced sealing cushions.

#### Complies with EN 352-1

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Median value (dB)	17,9	16,4	21,9	29,0	40,2	35,9	36,2	39,0
Standard deviation (dB)	5,4	4,1	3,8	4,0	4,9	3,3	5,8	6,1
Anticipated attenuation (dB)	12,5	12,3	18,1	25,0	35,3	32,6	30,4	32,9

H M L SNR 33 27 19 30

Code	Description	Туре	Colour	Unit	Pack
380682112	Hearing protection	402N	Black	PC	1
380684019	Hygiene kit	HK2		KIT	1
380684035	Comfort ring	CR1		BAG	1







## Hearing protection ZEKLER 403

Comfortable earmuffs with headband fitting with exceptional attenuation across medium and low frequencies. Headband fitting with fork-mount, and the wide sealing cushions make for an even head pressure and comfort.

- Attenuation level: Level 3
- Adjustable headband fitting.
- Soft, replacable head cushion.
- Wide, comfortable and easily replaced sealing cushions.

#### Complies with EN 352-1

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Median value (dB)	20,5	17,5	24,8	32,7	43,8	36,4	35,9	38,1
Standard deviation (dB)	5,4	3,0	2,4	2,6	3,7	3,5	3,1	4,1
Anticipated attenuation (dB)	15,1	14,5	22,4	30,1	40,1	32,9	32,8	34,0

H M L SNR 34 31 22 33

Code	Description	Туре	Colour	Unit	Pack
380682120	Hearing protection	403	Black	PC	1
380684019	Hygiene kit	HK2		KIT	1
380684035	Comfort ring	CR1		BAG	1







## Hearing protection ZEKLER 403H

Comfortable earnuffs hard hat attachment with exceptional attenuation across medium and low frequencies. The hard hat attachment with fork-mount and the wide sealing cushions give a constant head presure and comfortable use. Helmet adapter prepared for mounting the Zekler visor system.

- Attenuation level: Level 3
- For hard hat attachment.
- Helmet adapter prepared for mounting the Zekler visor system.
- Wide, comfortable and easily replaced sealing cushions.

Approved for mounting on the following safety helmets: IRIS 2, Style 300, Style 600, Balance AC, Balance HD, Peltor G2000, Peltor G3000, Uvex Airwing, Uvex Pheos, Uvex Pheos Alpine, JSP EVO2, EVO3, MK7 and LAS Rockman S14, S16 och S17.


#### Complies with EN 352-3

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Median value (dB)	16,4	17,7	23,5	31,8	41,6	36,4	34,2	35,2
Standard deviation (dB)	4,3	3,3	4,2	3,5	3,4	3,8	3,9	5,7
Anticipated attenuation (dB)	12,1	14,4	19,3	28,3	38,2	32,6	30,3	29,5

H M L SNR 32 29 21 31

Code	Description	Туре	Colour	Unit	Pack
380682138	Hearing protection	403H	Black	PC	1
380684019	Hygiene kit	HK2		KIT	1
380684035	Comfort ring	CR1		BAG	1





# Hearing protection ZEKLER 412RDB

Comfortable earmuffs with built-in FM stereo radio, level-dependent monitoring function and Bluetooth® wireless technology for connection to telephone and for streaming music. Music streaming pauses and the FM radio is lowered for incoming calls; for safety reasons the level-dependent monitoring function is retained. Good attenuation for low, high and medium frequencies. Headband with fork-mounting and the wide sealing cushions give a constant head pressure and comfortable use.

- Bluetooth® wireless technology for communication with mobile phone, laptop, iPad.
- Boom microphone with very effective noise suppression for clear communication even in noisy environments.
- "Side Tone" function enabling your voice to be heard clearly and to help you speak in a normal conversational level even in very noisy environments.Level-dependent monitoring function is retained for incoming calls for safety reasons.
- Adaptive Volume Control" function automatically adjusts the volume of incoming calls based on the surrounding noise level.
- FM stereo radio 88 108 MHz with volume limiter (82dB(A)).
- "Automatic Frequency Control" (AFC) reduces the noise between radio channels when
  - searching, locks and memorises selected channel even in lower reception areas.
- Automatic switching between Stereo/Mono for a more stable sound depending on reception conditions.



Level-dependent monitoring function Level Dependent System amplifies weaker sound and

allows you to hear your surroundings whilst keeping you protected from high impulse sounds.

- Attenuation: Level 2.
- 3,5 mm AUX input.
- Cable with 2 x 3,5 mm stereo plugs included.
- Adjustable headband.
- Soft, replaceable head cushion.
- Wide, comfortable and easily replaced sealing cushions.
- Up to 10 m range using Bluetooth® unit.
- Supplied with 2 x 1,5V AA batteries.
- Rechargeable batteries (HR6 2100 mAh) and battery charger available as accessories.
- Charges in around 3 hours from wall socket and around 8 hours in USB socket.
- Operational time up to 23 hours with all functions active.
- Battery status/energy saving for automatic switch-off if no settings have changed within 6 hours.

#### Complies with EN 352-1, 352-4, 352-6, 352-8 and EMC-directive 89/336/EEC.

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Average value (dB)	21	18,4	21,1	27,7	36,9	36,1	42,1	38,8
Standard deviation (dB)	6,3	4,5	4,2	3,5	4	3,6	3,5	5,4
Anticipated attenuation (dB)	14,7	13,9	16,9	24,2	32,9	32,5	38,6	33,4

Code	Description	Туре	Colou r	Uni t	Content s	Pac k
3806821 61	Hearing protection	412RDB	Black	PA C	1	1
3806822 58	Hearing protection	412RDB Colour Edi- tion	Blue	PC S		1
3806840 68	Rechargeable AA (HR6) batteries	HR6			1	1
3806841 00	Universal battery charger with USB cable			PA C	1	1
3806840 76	Complete boom mike				1	1
3806840 84	Wind guard for boom mike				1	1
3806840 92	Wind guard for monitoring mike				1	1
3806840 43	Connection cable 3.5 mm x 2				1	1
3806840 27	Hygiene kit	НКЗ		PA C	1	1
3806841 18	Hygiene kit	НКЗВ		PA C	1	1
3806840 35	Comfort ring	CR1			20	1







## Hearing protection ZEKLER 412RDBH

Comfortable earmuffs with built-in FM stereo radio, level-dependent monitoring function and Bluetooth® wireless technology for connection to telephone and for streaming music. Music streaming pauses and the FM radio is lowered for incoming calls; for safety reasons the monitoring function is retained. Good attenuation for low, high and medium frequencies. The hard hat attachment with fork-mounting and the wide sealing cushions give a constant head pressure and comfortable use. The helmet adapter is prepared for mounting the Zekler visor system.

- Bluetooth® wireless technology for communication with mobile phone, laptop, iPad.
- Boom microphone with very effective noise suppression for clear communication even in noisy environments.
- "Side Tone" function enabling your voice to be heard clearly and to help you speak in a normal conversational level even in very noisy environments.
- Level-dependent monitoring function is retained for incoming calls for safety reasons.
- "Adaptive Volume Control" function automatically adjusts the volume of incoming calls based on the surrounding noise level.
- FM stereo radio 88 108 MHz with volume limiter (82dB(A)).
- "Automatic Frequency Control" (AFC) reduces the noise between radio channels when searching, locks and memorises selected channel even in lower reception areas.
- Automatic switching between Stereo/Mono for a more stable sound depending on reception conditions.
- Level-dependant monitoring function Level Dependent System amplifies weaker sound and

allows you to hear your surroundings whilst keeping you protected from high impulse sounds.

- Attenuation: Level 2.
- 3,5 mm AUX input.
- Cable with 2 x 3,5 mm stereo plugs included.
- For hard hat attachment.
- Helmet adapter prepared for mounting the Zekler visor system.

Marketed by Skydda, Northern Europe's leading concept with Personal Protection Equipment www.skydda.com



- Wide, comfortable and easily replaced sealing cushions.
- Up to 10m range using Bluetooth® unit.
- Supplied with 2 x 1,5V AA batteries.
- Rechargeable batteries (HR6 2100 mAh) and battery charger available as accessories.

Charges in around 3 hours from wall socket and around 8 hours in USB socket.

- Operational time up to 23 hours with all functions active.
- Battery status/energy saving for automatic switch-off if no settings have changed within 6 hours.

Complies with EN 352-1, 352-3, 352-4, 352-6, 352-8 and the EMC-Directive 89/ 336/EEC.

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Average value (dB)	17,8	16,3	19,5	26,9	34,3	33,8	41,8	37,4
Standard deviation (dB)	4,2	4	3,2	3,1	4	2,9	3,3	3,8
Anticipated attenuation (dB)	13,6	12,3	16,3	23,8	30,3	30,9	38,5	33,6

Code	Description	Туре	Colo ur	Uni t	Content s	Pac k
3806821 79	Hearing protection	412RDB H	Black	PA C	1	1
3806840 68	Rechargeable AA (HR6) batteries	HR6			1	1
3806841 00	Universal battery charger with USB-cable			PA C	1	1
3806840 76	Complete boom microphone				1	1
3806840 84	Wind shield for boom microphone				1	1
3806840 92	Wind shield level-dependent monitoring microphone				1	1
3806840 43	Cable 3,5 mm x 2				1	1
3806841 18	Hygiene kit	НК3В		PA C	1	1
3806840 35	Comfort ring	CR1			20	1





# Hearing protection ZEKLER 412DB

Comfortable earmuffs with level-dependent monitoring function and Bluetooth® wireless technology for connection to telephone and for streaming music. Music streaming pauses for incoming calls; for safety reasons the level-dependent monitoring function is retained. Good attenuation for low, high and medium frequencies. Headband with forkmounting and the wide sealing cushions give a constant head pressure and comfortable use.

- Bluetooth® wireless technology for communication with mobile phone, laptop, iPad.
- Boom microphone with very effective noise suppression for clear communication even in noisy environments.
- "Side Tone" function enabling your voice to be heard clearly and to help you speak in a normal conversational level even in very noisy environments.
- Level-dependent monitoring function is retained for incoming calls for safety reasons.
- "Adaptive Volume Control" function automatically adjusts the volume of incoming calls based on the surrounding noise level.
- Level-dependant monitoring function Level Dependent System amplifies weaker sound and allows you to hear your surroundings whilst keeping you protected from high impulse sounds.
- Attenuation: Level 2.
- 3,5 mm AUX input.
- Cable with 2 x 3,5 mm stereo plugs included.
- Adjustable headband.
- Soft, replaceable head cushion.
- Wide, comfortable and easily replaced sealing cushions.
- Up to 10 m range using Bluetooth® unit.
- Supplied with 2 x 1,5V AA batteries.
- Rechargeable batteries (HR6 2100 mAh) and battery charger available as accessories.
  - Charges in around 3 hours from wall socket and around 8 hours in USB socket.
- Operational time up to 23 hours with all functions active.



• Battery status/energy saving for automatic switch-off if no settings have changed within 6 hours.

### Complies with EN 352-1, 352-4, 352-6, 352-8 and EMC-directive 89/336/EEC.

Frequency H		63	125	250	500	1000	200	-		8000
Average val	ue (dB)	21	18,4	21,1	27,7	36,9	36,	1	42,1	38,8
Standard de	viation (dB)	6,3	4,5	4,2	3,5	4	3,6		3,5	5,4
Anticipated	attenuation (dB)	14,7	13,9	16,9	24,2	32,9	32,5	5	38,6	33,4
Code	Description					Туре	Colo ur	Uni t	Content s	t Pac k
3806821 87	Hearing protection					412D B	Black	PA C	1	1
3806840 68	Rechargeable AA (HR6) bat	teries				HR6			1	1
3806841 00	Universal battery charger wit	h USB-	cable					PA C	1	1
3806840 76	Complete boom microphone								1	1
3806840 84	Wind shield for boom microp	hone							1	1
3806840 92	Wind shield for level-depend	ent mor	nitoring r	nicropho	ne				1	1
3806840 43	Cable 3,5 mm x 2								1	1
3806841 18	Hygiene kit					НК3 В		PA C	1	1
3806840 35	Comfort ring					CR1			20	1





### Hearing protection ZEKLER 412DBH

Comfortable hearing protection with built-in FM stereo radio, level-dependent monitoring and Bluetooth® wireless technology for connection to telephone and for streaming music. Music streaming pauses and the FM radio is lowered for incoming calls; for safety reasons the monitoring function is retained. Good attenuation for low, high and medium frequencies. The hard hat attachment with fork-mounting and the wide sealing cushions give a constant head pressure and comfortable use. The helmet adapter is prepared for mounting the Zekler visor system.

- Bluetooth® wireless technology for communication with mobile phone, laptop, iPad.
- Boom microphone with very effective noise suppression for clear communication even in noisy environments.
- "Side Tone" function enabling your voice to be heard clearly and to help you speak in a normal conversational level even in very noisy environments.
- Level-dependent monitoring function is retained for incoming calls for safety reasons.
- "Adaptive Volume Control" function automatically adjusts the volume of incoming calls based on the surrounding noise level.
- Level-dependant monitoring function Level Dependent System amplifies weaker sound and
- allows you to hear your surroundings whilst keeping you protected from high impulse sounds.
- Attenuation: Level 2.
- 3,5 mm AUX input.
- Cable with 2 x 3,5 mm stereo plugs included.



- For hard hat attachment.
- Helmet adapter prepared for mounting the Zekler visor system.
- Wide, comfortable and easily replaced sealing cushions.
- Up to 10m range using Bluetooth® unit.
- Supplied with 2 x 1,5V AA batteries.
- Rechargeable batteries (HR6 2100 mAh) and battery charger available as accessories. Charges in around 3 hours from wall socket and around 8 hours in USB socket.
- Operational time up to 23 hours with all functions active.
- Battery status/energy saving for automatic switch-off if no settings have changed within 6 hours.

# Complies with EN 352-1, 352-3, 352-4, 352-6, 352-8 and the EMC-Directive 89/ 336/EEC.

Frequency H	Z	63	125	250	500	1000	2000	400	0 8	000
Average valu	e (dB)	17,8	16,3	19,5	26,9	34,3	33"8	41,8	3 3	7,4
Standard dev	riation (dB)	4,2	4	3,2	3,1	4	2,9	3,3	3	,8
Anticipated a	ttenuation (dB)	13,6	12,3	16,3	23,8	30,3	30,9	38,5	5 3	3,6
Н	М		L			SNR				
33	26		19			29				
Code	Description						Туре	Colou r	Unit	Pac k
38068219 5	Hearing protection					4	H12DH B	Black	PAC	1
38068406 8	Rechargeable AA (HR6) b	atteries					HR6			1
38068410 0	Universal battery charger v	vith USB	-cable						PAC	1
38068407 6	Complete boom microphor	ne								1
38068408 4	Wind shield for boom micro	ophone								1
38068409 2	Wind shield for level-deper	ndent mo	onitoring	micropho	one					1
38068404 3	Cable 3,5 mm x 2									1
38068411 8	Hygiene kit						НК3В		PAC	1
38068403 5	Comfort ring						CR1			1





# Hearing protection ZEKLER 412RDB incl. battery and charger

Comfortable hearing protection incl battery and charger with built-in FM stereo radio, level-dependent monitoring function and Bluetooth® wireless technology for connection to telephone and for streaming music. Music streaming pauses and the FM radio is lowered for incoming calls; for safety reasons the level-dependent monitoring function is retained. Good attenuation for low, high and medium frequencies. Headband with fork-mounting and the wide sealing cushions give a constant head pressure and comfortable use.

- Bluetooth® wireless technology for communication with mobile phone, laptop, iPad.
- Boom microphone with very effective noise suppression for clear communication even in noisy environments.
- "Side Tone" function enabling your voice to be heard clearly and to help you speak in a normal conversational level even in very noisy environments.Level-dependent monitoring function is retained for incoming calls for safety reasons.
- Adaptive Volume Control" function automatically adjusts the volume of incoming calls based on the surrounding noise level.
- FM stereo radio 88 108 MHz with volume limiter (82dB(A)).
- "Automatic Frequency Control" (AFC) reduces the noise between radio channels
   when
- searching, locks and memorises selected channel even in lower reception areas.
  Automatic switching between Stereo/Mono for a more stable sound depending on reception conditions.

Level-dependent monitoring function Level Dependent System amplifies weaker sound and

- allows you to hear your surroundings whilst keeping you protected from high impulse sounds.
- Attenuation: Level 2.
- 3,5 mm AUX input.
- Cable with 2 x 3,5 mm stereo plugs included.



- Adjustable headband.
- Soft, replaceable head cushion.
- Wide, comfortable and easily replaced sealing cushions.
- Up to 10 m range using Bluetooth® unit.
- Supplied with rechargeable batteries (HR6 2100 mAh) and battery charger. Charges in around 3 hours from wall socket and around 8 hours in USB socket.
- Operational time up to 23 hours with all functions active.
- Battery status/energy saving for automatic switch-off if no settings have changed within 6 hours.

Complies with EN 352-1, 352-4, 352-6, 352-8 and EMC-directive 2004/108/EC.

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Average value (dB)	21	18,4	21,1	27,7	36,9	36,1	42,1	38,8
Standard deviation (dB)	6,3	4,5	4,2	3,5	4	3,6	3,5	5,4
Anticipated attenuation (dB)	14,7	13,9	16,9	24,2	32,9	32,5	38,6	33,4

Code	Description	Туре	Colo ur	Uni t	Content s	Pac k
3806822 00	Hearing protection with rechargeable batteries and charger	412RD B	Black	PA C	1	1
3806840 76	Complete boom mike				1	1
3806840 84	Wing guard for boom mike				1	1
3806840 92	Wind guard for monitoring mike				1	1
3806840 43	Connection cable 3.5 mm x 2				1	1
3806841 18	Hygiene kit	НК3B		PA C	1	1
3806840 35	Comfort ring	CR1			20	1





## Hearing protection ZEKLER 412S

Streaming ear cups for helmet mounting with sound quality as with headphones and without compromising on protection. The built-in microphone is designed to be used when you can turn off or leave the noisy environment.

- Bluetooth® range 10 metres
- Easy operation with buttons: Play, pause, next, previous, answer/reject incoming call, end call, volume up/down
- EPS (Electronic Protection System) restricts audio in the speakers to safe levels
- Built-in lithium ion battery provides up to 38 hours of uptime
- Adjustable headband with soft, replaceable head cushion
- USB charging cable included

# Complies to the PPE Directive 89/686 EEC, the PPE regulation 2016/425, EN 352-1, EN 352-8 and RED 2014/53/EU.

Frequency Hz		63	125	250	500	1000	2000	4000	8000
Average value (	(dB)	16,4	14,8	20,9	27,9	31,9	35,4	38,6	39,3
Standard deviat	tion (dB)	4,6	5,1	2,5	4,3	3,3	3,5	3,9	5,3
Anticipated atte	enuation (dB)	11,8	9,7	18,4	23,6	28,6	31,9	34,6	34
Code	Description			T	уре	Colour	Unit	Contents	Pack
380682300	Ear defender 412S					Black	PAC	1	10*
380684100	Battery charge inkl u	sb cabl	е				PAC	1	1
380684035	Comfort ring			(	CR1			20	1
380684118	Hygiene kit			Н	КЗВ		PAC	1	1





## Hearing protection ZEKLER 412SH

Streaming ear cups for helmet mounting with sound quality as with headphones and without compromising on protection. The built-in microphone is designed to be used when you can turn off or leave the noisy environment.

- Bluetooth® range 10 metres
- Easy operation with buttons: Play, pause, Next, Previous, answer/reject incoming call, end call, volume up/down
- · EPS (Electronic Protection System) restricts audio in the speakers to safe levels
- Built-in lithium ion battery provides up to 38 hours of uptime
- · Hard hat adapter prepared for mounting the Zekler visor system
- USB charging cable included

# Complies to the PPE Directive 89/686 EEC, the PPE regulation 2016/425, EN 352-3, EN 352-8 and RED 2014/53/EU.

Frequency Hz		63	125	250	500	1000	2000	4000	8000
Average value	rage value (dB) 11			20,4	26	30	33,7	39,7	36,2
Standard deviation (dB)			3,1	3,2	4,1	3	4,1	5,7	5,3
Anticipated atte	enuation (dB)	10	12,5	17,2	21,9	27	29,6	34	30,9
Н	М		L			SN	R		
31	25		1	9		28			
Code	Description			٦	Гуре	Colour	Unit	Contents	Pack
380682305	Ear defender 412SH					Black	PAC	1	10*
380684100	Battery charge inkl us	o cable					PAC	1	1
380684035	Comfort ring			(	CR1			20	1
380684118	Hygiene kit			Н	КЗВ		PAC	1	1







# Hearing protection ZEKLER 401H

Comfortable earnuffs with hard hat attachment. Particularly good attenuation across medium and high frequencies. The hard hat attachment with fork-mount and the wide sealing cushions give a constant head presure and comfortable use. Especially suited in lower ambient noise level environments. Helmet adapter prepared for mounting the Zekler visor system.

- Attenuation level: Level 1
- For hard hat attachment.
- Helmet adapter prepared for mounting the Zekler visor system.
- Wide, cocmfortable and easily replaced sealing cushions.

Approved for mounting on the following safety helmets: IRIS 2, Style 300, Style 600, Balance AC, Balance HD, Peltor G2000, Peltor G3000, Uvex Airwing, Uvex Pheos, Uvex Pheos Alpine, JSP EVO2, EVO3, MK7 and LAS Rockman S14, S16 och S17.

#### Complies with EN 352-3

Frequ	uency H	Z			63	125	250	500	1000	2000	4000	8000
Medi	an value	: (dB)			15,0	15,0	14,7	24,7	33,1	26,8	32,2	34,6
Standard deviation (dB)			4,2	3,1	2,9	2,9	3,2	2,7	2,8	3,7		
Antic	ipated a	ttenuati	on (dB)		10,8	11,9	11,8	21,8	29,9	24,1	29,4	30,9
Н	М	L	SNR									
24	23	16	25									
Cod	е		Desci	iption			٦	Гуре	Colo	ur	Unit	Pack
380	582070		Hearir	g protectior	า		4	01H	Blac	k	PC	1
380	584001		Hygier	ne kit			ŀ	HK1			KIT	1
380	684035		Comfo	ort ring			(	CR1			BAG	1







## Hearing protection ZEKLER 403H

Comfortable earnuffs hard hat attachment with exceptional attenuation across medium and low frequencies. The hard hat attachment with fork-mount and the wide sealing cushions give a constant head presure and comfortable use. Helmet adapter prepared for mounting the Zekler visor system.

- Attenuation level: Level 3
- For hard hat attachment.
- Helmet adapter prepared for mounting the Zekler visor system.
- Wide, comfortable and easily replaced sealing cushions.

Approved for mounting on the following safety helmets: IRIS 2, Style 300, Style 600, Balance AC, Balance HD, Peltor G2000, Peltor G3000, Uvex Airwing, Uvex Pheos, Uvex Pheos Alpine, JSP EVO2, EVO3, MK7 and LAS Rockman S14, S16 och S17.

#### Complies with EN 352-3

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Median value (dB)	16,4	17,7	23,5	31,8	41,6	36,4	34,2	35,2
Standard deviation (dB)	4,3	3,3	4,2	3,5	3,4	3,8	3,9	5,7
Anticipated attenuation (dB)	12,1	14,4	19,3	28,3	38,2	32,6	30,3	29,5

H M L SNR 32 29 21 31

Code	Description	Туре	Colour	Unit	Pack
380682138	Hearing protection	403H	Black	PC	1
380684019	Hygiene kit	HK2		KIT	1
380684035	Comfort ring	CR1		BAG	1





# Hearing protection ZEKLER 412DH

Comfortable earmuffs with built-in stereo FM radio and level-dependent monitoring function. The microphones on the cups' front take in the ambient sound so that you can hear what's happening around you and facilitate communication with your workmates. If the noise comes up to dangerous levels the electronics react straight away and reduce the level to max 82 dB(A). A great aid in environments with impulse noise or varying noise levels. Fitted with a 3.5 mm aux audio input channel for connecting an MP3 player, for example. Good noise reduction over low. medium and high frequencies. The headband fitting has a fork-mount and the wide sealing cushions make for an even head pressure and comfort.

- Attenuation level: Level 2.
- Level-dependent monitoring function, Level Dependent System.
- 3.5 mm AUX input.
- Cable with 2x3.5 mm stereo plugs included.
- 2 x 1.5V AA batteries operation time around 120 hours.
- Adjustable head fitting.
- For hard hat attachment.
- Soft, replaceable head cushion.
- Wide, comfortable and easily replaced sealing cushions.

Approved for mounting on the following safety helmets: IRIS 2, Style 300, Style 600, Balance AC, Balance HD, Peltor G2000 och Peltor G3000 Complies with EN 352-3, 352-4, 352-6



Frequency Hz	63	125	250	500	1000	2000	4000	8000
Median vlaue (dB)	17,8	16,3	19,5	26,9	34,3	33,8	41,8	37,4
Standard deviation (dB)	4,2	4	3,2	3,1	4	2,9	3,3	3,8
Anticipated attenuation (dB)	13,6	12,3	16,3	23,8	30,3	30,9	38,5	33,6

 H
 M
 L
 SNR

 33
 26
 19
 29

Code	Description	Туре	Colour	Unit	Pack
380682054	Hearing protection	412DH	Black	PC	1
380684027	Hygiene kit	НКЗ		KIT	1
380684035	Comfort ring	CR!		BAG	1
380684043	Cable 3,5 mm x 2				
380684092	Wind shield for monitoring microphone				

Marketed by Skydda, Northern Europe's leading concept with Personal Protection Equipment www.skydda.com







## Hearing protection ZEKLER 403H

Comfortable earnuffs hard hat attachment with exceptional attenuation across medium and low frequencies. The hard hat attachment with fork-mount and the wide sealing cushions give a constant head presure and comfortable use. Helmet adapter prepared for mounting the Zekler visor system.

- Attenuation level: Level 3
- For hard hat attachment.
- Helmet adapter prepared for mounting the Zekler visor system.
- Wide, comfortable and easily replaced sealing cushions.

Approved for mounting on the following safety helmets: IRIS 2, Style 300, Style 600, Balance AC, Balance HD, Peltor G2000, Peltor G3000, Uvex Airwing, Uvex Pheos, Uvex Pheos Alpine, JSP EVO2, EVO3, MK7 and LAS Rockman S14, S16 och S17.

#### Complies with EN 352-3

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Median value (dB)	16,4	17,7	23,5	31,8	41,6	36,4	34,2	35,2
Standard deviation (dB)	4,3	3,3	4,2	3,5	3,4	3,8	3,9	5,7
Anticipated attenuation (dB)	12,1	14,4	19,3	28,3	38,2	32,6	30,3	29,5

H M L SNR 32 29 21 31

Code	Description	Туре	Colour	Unit	Pack
380682138	Hearing protection	403H	Black	PC	1
380684019	Hygiene kit	HK2		KIT	1
380684035	Comfort ring	CR1		BAG	1





### Hearing protection ZEKLER 412DBH

Comfortable hearing protection with built-in FM stereo radio, level-dependent monitoring and Bluetooth® wireless technology for connection to telephone and for streaming music. Music streaming pauses and the FM radio is lowered for incoming calls; for safety reasons the monitoring function is retained. Good attenuation for low, high and medium frequencies. The hard hat attachment with fork-mounting and the wide sealing cushions give a constant head pressure and comfortable use. The helmet adapter is prepared for mounting the Zekler visor system.

- Bluetooth® wireless technology for communication with mobile phone, laptop, iPad.
- Boom microphone with very effective noise suppression for clear communication even in noisy environments.
- "Side Tone" function enabling your voice to be heard clearly and to help you speak in a normal conversational level even in very noisy environments.
- Level-dependent monitoring function is retained for incoming calls for safety reasons.
- "Adaptive Volume Control" function automatically adjusts the volume of incoming calls based on the surrounding noise level.
- Level-dependant monitoring function Level Dependent System amplifies weaker sound and
- allows you to hear your surroundings whilst keeping you protected from high impulse sounds.
- Attenuation: Level 2.
- 3,5 mm AUX input.
- Cable with 2 x 3,5 mm stereo plugs included.



- For hard hat attachment.
- Helmet adapter prepared for mounting the Zekler visor system.
- Wide, comfortable and easily replaced sealing cushions.
- Up to 10m range using Bluetooth® unit.
- Supplied with 2 x 1,5V AA batteries.
- Rechargeable batteries (HR6 2100 mAh) and battery charger available as accessories. Charges in around 3 hours from wall socket and around 8 hours in USB socket.
- Operational time up to 23 hours with all functions active.
- Battery status/energy saving for automatic switch-off if no settings have changed within 6 hours.

Frequency H	Z	63	125	250	500	1000	2000	400	0 8	000
Average valu	e (dB)	17,8	16,3	19,5	26,9	34,3	33"8	41,8	3 3	7,4
Standard dev	riation (dB)	4,2	4	3,2	3,1	4	2,9	3,3	3	,8
Anticipated a	ttenuation (dB)	13,6	12,3	16,3	23,8	30,3	30,9	38,5	5 3	3,6
Н	М		L			SNR				
33	26		19			29				
Code	Description						Туре	Colou r	Unit	Pac k
38068219 5	Hearing protection					4	H12DH B	Black	PAC	1
38068406 8	Rechargeable AA (HR6) b	atteries					HR6			1
38068410 0	Universal battery charger v	vith USB	-cable						PAC	1
38068407 6	Complete boom microphor	ne								1
38068408 4	Wind shield for boom micro	ophone								1
38068409 2	Wind shield for level-deper	ndent mo	onitoring	micropho	one					1
38068404 3	Cable 3,5 mm x 2									1
38068411 8	Hygiene kit						НК3В		PAC	1
38068403 5	Comfort ring						CR1			1





- Bluetooth® wireless technology for communication with mobile phone, laptop, iPad.
- Boom microphone with very effective noise suppression for clear communication even in noisy environments.
- "Side Tone" function enabling your voice to be heard clearly and to help you speak in a normal conversational level even in very noisy environments.
- Level-dependent monitoring function is retained for incoming calls for safety reasons.
- "Adaptive Volume Control" function automatically adjusts the volume of incoming calls based on the surrounding noise level.
- Level-dependant monitoring function Level Dependent System amplifies weaker sound and
- allows you to hear your surroundings whilst keeping you protected from high impulse sounds.
- Attenuation: Level 2.
- 3,5 mm AUX input.
- Cable with 2 x 3,5 mm stereo plugs included.



- For hard hat attachment.
- Helmet adapter prepared for mounting the Zekler visor system.
- Wide, comfortable and easily replaced sealing cushions.
- Up to 10m range using Bluetooth® unit.
- Supplied with 2 x 1,5V AA batteries.
- Rechargeable batteries (HR6 2100 mAh) and battery charger available as accessories. Charges in around 3 hours from wall socket and around 8 hours in USB socket.
- Operational time up to 23 hours with all functions active.
- Battery status/energy saving for automatic switch-off if no settings have changed within 6 hours.

Frequency H	Z	63	125	250	500	1000	2000	400	0 8	000
Average valu	e (dB)	17,8	16,3	19,5	26,9	34,3	33"8	41,8	3 3	7,4
Standard dev	riation (dB)	4,2	4	3,2	3,1	4	2,9	3,3	3	,8
Anticipated a	ttenuation (dB)	13,6	12,3	16,3	23,8	30,3	30,9	38,5	5 3	3,6
Н	М		L			SNR				
33	26		19			29				
Code	Description						Туре	Colou r	Unit	Pac k
38068219 5	Hearing protection					4	H12DH B	Black	PAC	1
38068406 8	Rechargeable AA (HR6) b	atteries					HR6			1
38068410 0	Universal battery charger v	vith USB	-cable						PAC	1
38068407 6	Complete boom microphor	ne								1
38068408 4	Wind shield for boom micro	ophone								1
38068409 2	Wind shield for level-deper	ndent mo	onitoring	micropho	one					1
38068404 3	Cable 3,5 mm x 2									1
38068411 8	Hygiene kit						НК3В		PAC	1
38068403 5	Comfort ring						CR1			1





- Bluetooth® wireless technology for communication with mobile phone, laptop, iPad.
- Boom microphone with very effective noise suppression for clear communication even in noisy environments.
- "Side Tone" function enabling your voice to be heard clearly and to help you speak in a normal conversational level even in very noisy environments.
- Level-dependent monitoring function is retained for incoming calls for safety reasons.
- "Adaptive Volume Control" function automatically adjusts the volume of incoming calls based on the surrounding noise level.
- Level-dependant monitoring function Level Dependent System amplifies weaker sound and
- allows you to hear your surroundings whilst keeping you protected from high impulse sounds.
- Attenuation: Level 2.
- 3,5 mm AUX input.
- Cable with 2 x 3,5 mm stereo plugs included.



- For hard hat attachment.
- Helmet adapter prepared for mounting the Zekler visor system.
- Wide, comfortable and easily replaced sealing cushions.
- Up to 10m range using Bluetooth® unit.
- Supplied with 2 x 1,5V AA batteries.
- Rechargeable batteries (HR6 2100 mAh) and battery charger available as accessories. Charges in around 3 hours from wall socket and around 8 hours in USB socket.
- Operational time up to 23 hours with all functions active.
- Battery status/energy saving for automatic switch-off if no settings have changed within 6 hours.

Frequency H	Z	63	125	250	500	1000	2000	400	0 8	000
Average valu	e (dB)	17,8	16,3	19,5	26,9	34,3	33"8	41,8	3 3	7,4
Standard dev	riation (dB)	4,2	4	3,2	3,1	4	2,9	3,3	3	,8
Anticipated a	ttenuation (dB)	13,6	12,3	16,3	23,8	30,3	30,9	38,5	5 3	3,6
Н	М		L			SNR				
33	26		19			29				
Code	Description						Туре	Colou r	Unit	Pac k
38068219 5	Hearing protection					4	H12DH B	Black	PAC	1
38068406 8	Rechargeable AA (HR6) b	atteries					HR6			1
38068410 0	Universal battery charger v	vith USB	-cable						PAC	1
38068407 6	Complete boom microphor	ne								1
38068408 4	Wind shield for boom micro	ophone								1
38068409 2	Wind shield for level-deper	ndent mo	onitoring	micropho	one					1
38068404 3	Cable 3,5 mm x 2									1
38068411 8	Hygiene kit						НК3В		PAC	1
38068403 5	Comfort ring						CR1			1





- Bluetooth® wireless technology for communication with mobile phone, laptop, iPad.
- Boom microphone with very effective noise suppression for clear communication even in noisy environments.
- "Side Tone" function enabling your voice to be heard clearly and to help you speak in a normal conversational level even in very noisy environments.
- Level-dependent monitoring function is retained for incoming calls for safety reasons.
- "Adaptive Volume Control" function automatically adjusts the volume of incoming calls based on the surrounding noise level.
- Level-dependant monitoring function Level Dependent System amplifies weaker sound and
- allows you to hear your surroundings whilst keeping you protected from high impulse sounds.
- Attenuation: Level 2.
- 3,5 mm AUX input.
- Cable with 2 x 3,5 mm stereo plugs included.



- For hard hat attachment.
- Helmet adapter prepared for mounting the Zekler visor system.
- Wide, comfortable and easily replaced sealing cushions.
- Up to 10m range using Bluetooth® unit.
- Supplied with 2 x 1,5V AA batteries.
- Rechargeable batteries (HR6 2100 mAh) and battery charger available as accessories. Charges in around 3 hours from wall socket and around 8 hours in USB socket.
- Operational time up to 23 hours with all functions active.
- Battery status/energy saving for automatic switch-off if no settings have changed within 6 hours.

Frequency H	Z	63	125	250	500	1000	2000	400	0 8	000
Average valu	e (dB)	17,8	16,3	19,5	26,9	34,3	33"8	41,8	3 3	7,4
Standard dev	riation (dB)	4,2	4	3,2	3,1	4	2,9	3,3	3	,8
Anticipated a	ttenuation (dB)	13,6	12,3	16,3	23,8	30,3	30,9	38,5	5 3	3,6
Н	М		L			SNR				
33	26		19			29				
Code	Description						Туре	Colou r	Unit	Pac k
38068219 5	Hearing protection					4	H12DH B	Black	PAC	1
38068406 8	Rechargeable AA (HR6) b	atteries					HR6			1
38068410 0	Universal battery charger v	vith USB	-cable						PAC	1
38068407 6	Complete boom microphor	ne								1
38068408 4	Wind shield for boom micro	ophone								1
38068409 2	Wind shield for level-deper	ndent mo	onitoring	micropho	one					1
38068404 3	Cable 3,5 mm x 2									1
38068411 8	Hygiene kit						НК3В		PAC	1
38068403 5	Comfort ring						CR1			1





- Bluetooth® wireless technology for communication with mobile phone, laptop, iPad.
- Boom microphone with very effective noise suppression for clear communication even in noisy environments.
- "Side Tone" function enabling your voice to be heard clearly and to help you speak in a normal conversational level even in very noisy environments.
- Level-dependent monitoring function is retained for incoming calls for safety reasons.
- "Adaptive Volume Control" function automatically adjusts the volume of incoming calls based on the surrounding noise level.
- Level-dependant monitoring function Level Dependent System amplifies weaker sound and
- allows you to hear your surroundings whilst keeping you protected from high impulse sounds.
- Attenuation: Level 2.
- 3,5 mm AUX input.
- Cable with 2 x 3,5 mm stereo plugs included.



- For hard hat attachment.
- Helmet adapter prepared for mounting the Zekler visor system.
- Wide, comfortable and easily replaced sealing cushions.
- Up to 10m range using Bluetooth® unit.
- Supplied with 2 x 1,5V AA batteries.
- Rechargeable batteries (HR6 2100 mAh) and battery charger available as accessories. Charges in around 3 hours from wall socket and around 8 hours in USB socket.
- Operational time up to 23 hours with all functions active.
- Battery status/energy saving for automatic switch-off if no settings have changed within 6 hours.

Frequency H	Z	63	125	250	500	1000	2000	400	0 8	000
Average valu	e (dB)	17,8	16,3	19,5	26,9	34,3	33"8	41,8	3 3	7,4
Standard dev	riation (dB)	4,2	4	3,2	3,1	4	2,9	3,3	3	,8
Anticipated a	ttenuation (dB)	13,6	12,3	16,3	23,8	30,3	30,9	38,5	5 3	3,6
Н	М		L			SNR				
33	26		19			29				
Code	Description						Туре	Colou r	Unit	Pac k
38068219 5	Hearing protection					4	H12DH B	Black	PAC	1
38068406 8	Rechargeable AA (HR6) b	atteries					HR6			1
38068410 0	Universal battery charger v	vith USB	-cable						PAC	1
38068407 6	Complete boom microphor	ne								1
38068408 4	Wind shield for boom micro	ophone								1
38068409 2	Wind shield for level-deper	ndent mo	onitoring	micropho	one					1
38068404 3	Cable 3,5 mm x 2									1
38068411 8	Hygiene kit						НК3В		PAC	1
38068403 5	Comfort ring						CR1			1





- Bluetooth® wireless technology for communication with mobile phone, laptop, iPad.
- Boom microphone with very effective noise suppression for clear communication even in noisy environments.
- "Side Tone" function enabling your voice to be heard clearly and to help you speak in a normal conversational level even in very noisy environments.
- Level-dependent monitoring function is retained for incoming calls for safety reasons.
- "Adaptive Volume Control" function automatically adjusts the volume of incoming calls based on the surrounding noise level.
- Level-dependant monitoring function Level Dependent System amplifies weaker sound and
- allows you to hear your surroundings whilst keeping you protected from high impulse sounds.
- Attenuation: Level 2.
- 3,5 mm AUX input.
- Cable with 2 x 3,5 mm stereo plugs included.



- For hard hat attachment.
- Helmet adapter prepared for mounting the Zekler visor system.
- Wide, comfortable and easily replaced sealing cushions.
- Up to 10m range using Bluetooth® unit.
- Supplied with 2 x 1,5V AA batteries.
- Rechargeable batteries (HR6 2100 mAh) and battery charger available as accessories. Charges in around 3 hours from wall socket and around 8 hours in USB socket.
- Operational time up to 23 hours with all functions active.
- Battery status/energy saving for automatic switch-off if no settings have changed within 6 hours.

Frequency H	Z	63	125	250	500	1000	2000	400	0 8	000
Average valu	e (dB)	17,8	16,3	19,5	26,9	34,3	33"8	41,8	3 3	7,4
Standard dev	riation (dB)	4,2	4	3,2	3,1	4	2,9	3,3	3	,8
Anticipated a	ttenuation (dB)	13,6	12,3	16,3	23,8	30,3	30,9	38,5	5 3	3,6
Н	М		L			SNR				
33	26		19			29				
Code	Description						Туре	Colou r	Unit	Pac k
38068219 5	Hearing protection					4	H12DH B	Black	PAC	1
38068406 8	Rechargeable AA (HR6) b	atteries					HR6			1
38068410 0	Universal battery charger v	vith USB	-cable						PAC	1
38068407 6	Complete boom microphor	ne								1
38068408 4	Wind shield for boom micro	ophone								1
38068409 2	Wind shield for level-deper	ndent mo	onitoring	micropho	one					1
38068404 3	Cable 3,5 mm x 2									1
38068411 8	Hygiene kit						НК3В		PAC	1
38068403 5	Comfort ring						CR1			1





- Bluetooth® wireless technology for communication with mobile phone, laptop, iPad.
- Boom microphone with very effective noise suppression for clear communication even in noisy environments.
- "Side Tone" function enabling your voice to be heard clearly and to help you speak in a normal conversational level even in very noisy environments.
- Level-dependent monitoring function is retained for incoming calls for safety reasons.
- "Adaptive Volume Control" function automatically adjusts the volume of incoming calls based on the surrounding noise level.
- Level-dependant monitoring function Level Dependent System amplifies weaker sound and
- allows you to hear your surroundings whilst keeping you protected from high impulse sounds.
- Attenuation: Level 2.
- 3,5 mm AUX input.
- Cable with 2 x 3,5 mm stereo plugs included.



- For hard hat attachment.
- Helmet adapter prepared for mounting the Zekler visor system.
- Wide, comfortable and easily replaced sealing cushions.
- Up to 10m range using Bluetooth® unit.
- Supplied with 2 x 1,5V AA batteries.
- Rechargeable batteries (HR6 2100 mAh) and battery charger available as accessories. Charges in around 3 hours from wall socket and around 8 hours in USB socket.
- Operational time up to 23 hours with all functions active.
- Battery status/energy saving for automatic switch-off if no settings have changed within 6 hours.

Frequency H	Z	63	125	250	500	1000	2000	400	0 8	000
Average valu	e (dB)	17,8	16,3	19,5	26,9	34,3	33"8	41,8	3 3	7,4
Standard dev	riation (dB)	4,2	4	3,2	3,1	4	2,9	3,3	3	,8
Anticipated a	ttenuation (dB)	13,6	12,3	16,3	23,8	30,3	30,9	38,5	5 3	3,6
Н	М		L			SNR				
33	26		19			29				
Code	Description						Туре	Colou r	Unit	Pac k
38068219 5	Hearing protection					4	H12DH B	Black	PAC	1
38068406 8	Rechargeable AA (HR6) b	atteries					HR6			1
38068410 0	Universal battery charger v	vith USB	-cable						PAC	1
38068407 6	Complete boom microphor	ne								1
38068408 4	Wind shield for boom micro	ophone								1
38068409 2	Wind shield for level-deper	ndent mo	onitoring	micropho	one					1
38068404 3	Cable 3,5 mm x 2									1
38068411 8	Hygiene kit						НК3В		PAC	1
38068403 5	Comfort ring						CR1			1







# Earplugs ZEKLER 802 S

Disposable earplug i size Small (S) to fit most ear canals. The material's composition allows the earplug a well-proportioned expansion. Robust, wall-mounted dispenser that holds 500 pairs of plugs available as an accessory.

- Conically formed disposable plug made from PU material, fully silicone-free.
- Dirt-repellent surface.
- Available in sizes Small (S) and Large (L) for best fit.
- Form and material composition enable the plug to acvieve a well-proportioned expansion.
- Sits snugly and tight wihtout putting pressure on the ear canal.



Frequency H	Z	63	125	250	500	1000	2000	4000	3000
Mean value (	dB)	28,9	31,0	33,6	33,8	33,6	36,2	40,06	44,3
Standard dev	riation (dB)	3,4	5,2	5,4	5,4	4,0	4,2	3,7	2,9
Anticipated a	ttenuation (dB)	25,5	25,8	28,2	28,4	29,6	32,0	36,9	41,4
						0115			
Н	М		L			SNR			
33	30		29			33			
Code	Description					Colour	Uni t	Contents	Pac k
38068800 2	802 S (1 pair/PP-bag, 200	) pairs/b	oox)			Red	PAC	200	1
38068802 8	802 S refill (300 pairs loos	e-packe	d/box)			Red	PAC	600	20*
38068798 8	802 S 10-PAC (10 pairs lo	ose pac	ked in re	-sealabl	e bag)	Red		20	25*
38068797 0	Dispenser for box 802 S repairs)	fill or 80	)2 L refil	l (space	for 500	Black/Re	ed PC S	1	3*







# Earplugs ZEKLER 802 S

Disposable earplug i size Small (S) to fit most ear canals. The material's composition allows the earplug a well-proportioned expansion. Robust, wall-mounted dispenser that holds 500 pairs of plugs available as an accessory.

- Conically formed disposable plug made from PU material, fully silicone-free.
- Dirt-repellent surface.
- Available in sizes Small (S) and Large (L) for best fit.
- Form and material composition enable the plug to acvieve a well-proportioned expansion.
- Sits snugly and tight wihtout putting pressure on the ear canal.



Frequency H	Z	63	125	250	500	1000	2000	4000	3000
Mean value (	dB)	28,9	31,0	33,6	33,8	33,6	36,2	40,06	44,3
Standard dev	riation (dB)	3,4	5,2	5,4	5,4	4,0	4,2	3,7	2,9
Anticipated a	ttenuation (dB)	25,5	25,8	28,2	28,4	29,6	32,0	36,9	41,4
						0115			
Н	М		L			SNR			
33	30		29			33			
Code	Description					Colour	Uni t	Contents	Pac k
38068800 2	802 S (1 pair/PP-bag, 200	) pairs/b	oox)			Red	PAC	200	1
38068802 8	802 S refill (300 pairs loos	e-packe	d/box)			Red	PAC	600	20*
38068798 8	802 S 10-PAC (10 pairs lo	ose pac	ked in re	-sealabl	e bag)	Red		20	25*
38068797 0	Dispenser for box 802 S repairs)	fill or 80	)2 L refil	l (space	for 500	Black/Re	ed PC S	1	3*







## Earplugs ZEKLER 802 L

Disposable earplug i size Small (S) and Large (L) to fit most ear canals. The material's composition allows the earplug a well-proportioned expansion. Zekler 802 L has a very even attenuation, providing a natural sound reproduction. Robust, wall-mounted dispenser that holds 500 pairs of plugs available as an accessory.

- Conically formed disposable plug made from PU material, fully silicone-free.
- Dirt-repellent surface.
- Available in sizes Small (S) and Large (L) for best fit.
- Form and material composition enable the plug to acvieve a well-proportioned expansion.
- Sits snugly and tight wihtout putting pressure on the ear canal.
- 802 L has a very even attenuation for a natural sound reproduction.



Frequency Hz		63	125	250	500	1000	2000	4000	8000
Mean value (c	IB)	35,3	38,4	39,3	40,8	38,9	37,8	45,9	45,1
Standard devi	ation (dB)	4,2	6,3	5,3	5,5	5,5	4,3	3,9	4,6
Anticipated at	tentuation (dB)	31,1	32,1	34,0	35,3	33,4	33,5	42,0	40,5
Н	М		L			SNR			
36	34		34			37			

36	34	34	37			
Code	Description		Cold	our Un it	Content s	Pac k
3806880 10	802 L (1 pair/PP-bag, 2	00 pairs/(box)	Re	d PA C	200	1
3806880 36	802 L refill (300 pairs lo	ose-packed/box)	Re	d PA C	600	20*
3806879 96	802 L 10-PAC (10 pairs	loos-packed in resealable bag)	Re	d	20	25*
3806879 70	Dispenser för box 802 S	refill or 802 L refill (space for 500 pa	airs) Blac Re		1	3*







# Earplugs ZEKLER 802 S

Disposable earplug i size Small (S) to fit most ear canals. The material's composition allows the earplug a well-proportioned expansion. Robust, wall-mounted dispenser that holds 500 pairs of plugs available as an accessory.

- Conically formed disposable plug made from PU material, fully silicone-free.
- Dirt-repellent surface.
- Available in sizes Small (S) and Large (L) for best fit.
- Form and material composition enable the plug to acvieve a well-proportioned expansion.
- Sits snugly and tight wihtout putting pressure on the ear canal.



Frequency H	Z	63	125	250	500	1000	2000	4000	3000
Mean value (	dB)	28,9	31,0	33,6	33,8	33,6	36,2	40,06	44,3
Standard dev	riation (dB)	3,4	5,2	5,4	5,4	4,0	4,2	3,7	2,9
Anticipated a	ttenuation (dB)	25,5	25,8	28,2	28,4	29,6	32,0	36,9	41,4
						0115			
Н	М		L			SNR			
33	30		29			33			
Code	Description					Colour	Uni t	Contents	Pac k
38068800 2	802 S (1 pair/PP-bag, 200	) pairs/b	oox)			Red	PAC	200	1
38068802 8	802 S refill (300 pairs loos	e-packe	d/box)			Red	PAC	600	20*
38068798 8	802 S 10-PAC (10 pairs lo	ose pac	ked in re	-sealabl	e bag)	Red		20	25*
38068797 0	Dispenser for box 802 S repairs)	fill or 80	)2 L refil	l (space	for 500	Black/Re	ed PC S	1	3*







## Earplugs ZEKLER 802 L

Disposable earplug i size Small (S) and Large (L) to fit most ear canals. The material's composition allows the earplug a well-proportioned expansion. Zekler 802 L has a very even attenuation, providing a natural sound reproduction. Robust, wall-mounted dispenser that holds 500 pairs of plugs available as an accessory.

- Conically formed disposable plug made from PU material, fully silicone-free.
- Dirt-repellent surface.
- Available in sizes Small (S) and Large (L) for best fit.
- Form and material composition enable the plug to acvieve a well-proportioned expansion.
- Sits snugly and tight wihtout putting pressure on the ear canal.
- 802 L has a very even attenuation for a natural sound reproduction.



Frequency Hz		63	125	250	500	1000	2000	4000	8000
Mean value (c	IB)	35,3	38,4	39,3	40,8	38,9	37,8	45,9	45,1
Standard devi	ation (dB)	4,2	6,3	5,3	5,5	5,5	4,3	3,9	4,6
Anticipated at	tentuation (dB)	31,1	32,1	34,0	35,3	33,4	33,5	42,0	40,5
Н	М		L			SNR			
36	34		34			37			

36	34	34	37			
Code	Description		Cold	our Un it	Content s	Pac k
3806880 10	802 L (1 pair/PP-bag, 2	00 pairs/(box)	Re	d PA C	200	1
3806880 36	802 L refill (300 pairs lo	ose-packed/box)	Re	d PA C	600	20*
3806879 96	802 L 10-PAC (10 pairs	loos-packed in resealable bag)	Re	d	20	25*
3806879 70	Dispenser för box 802 S	refill or 802 L refill (space for 500 pa	airs) Blac Re		1	3*







# Earplugs ZEKLER 802 S

Disposable earplug i size Small (S) to fit most ear canals. The material's composition allows the earplug a well-proportioned expansion. Robust, wall-mounted dispenser that holds 500 pairs of plugs available as an accessory.

- Conically formed disposable plug made from PU material, fully silicone-free.
- Dirt-repellent surface.
- Available in sizes Small (S) and Large (L) for best fit.
- Form and material composition enable the plug to acvieve a well-proportioned expansion.
- Sits snugly and tight wihtout putting pressure on the ear canal.



Frequency H	Z	63	125	250	500	1000	2000	4000	8000
Mean value (	dB)	28,9	31,0	33,6	33,8	33,6	36,2	40,06	44,3
Standard dev	riation (dB)	3,4	5,2	5,4	5,4	4,0	4,2	3,7	2,9
Anticipated a	ttenuation (dB)	25,5	25,8	28,2	28,4	29,6	32,0	36,9	41,4
Н	М		L			SNR			
33	30		29			33			
Code	Description					Colour	Uni t	Contents	Pac k
38068800 2	802 S (1 pair/PP-bag, 200	) pairs/b	oox)			Red	PAC	200	1
38068802 8	802 S refill (300 pairs loos	e-packe	d/box)			Red	PAC	600	20*
38068798 8	802 S 10-PAC (10 pairs loose packed in re-sealable bag)					Red		20	25*
38068797 0	Dispenser for box 802 S re pairs)	fill or 80	)2 L refil	l (space	for 500	Black/Re	ed PC S	1	3*







## Earplugs ZEKLER 802 L

Disposable earplug i size Small (S) and Large (L) to fit most ear canals. The material's composition allows the earplug a well-proportioned expansion. Zekler 802 L has a very even attenuation, providing a natural sound reproduction. Robust, wall-mounted dispenser that holds 500 pairs of plugs available as an accessory.

- Conically formed disposable plug made from PU material, fully silicone-free.
- Dirt-repellent surface.
- Available in sizes Small (S) and Large (L) for best fit.
- Form and material composition enable the plug to acvieve a well-proportioned expansion.
- Sits snugly and tight wihtout putting pressure on the ear canal.
- 802 L has a very even attenuation for a natural sound reproduction.



Frequency Hz		63	125	250	500	1000	2000	4000	8000
Mean value (c	IB)	35,3	38,4	39,3	40,8	38,9	37,8	45,9	45,1
Standard devi	ation (dB)	4,2	6,3	5,3	5,5	5,5	4,3	3,9	4,6
Anticipated at	tentuation (dB)	31,1	32,1	34,0	35,3	33,4	33,5	42,0	40,5
Н	М		L			SNR			
36	34		34			37			

36	34	34	37			
Code	Description		Cold	our Un it	Content s	Pac k
3806880 10	802 L (1 pair/PP-bag, 2	00 pairs/(box)	Re	d PA C	200	1
3806880 36	802 L refill (300 pairs lo	ose-packed/box)	Re	d PA C	600	20*
3806879 96	802 L 10-PAC (10 pairs	loos-packed in resealable bag)	Re	d	20	25*
3806879 70	Dispenser för box 802 S	refill or 802 L refill (space for 500 pa	airs) Blac Re		1	3*







## Earplugs ZEKLER 922 L

Reusable earplug in a universal size. The plug has a stiff shaft but soft, pliable fins which facilitate insertion. The material softens in contact with body temperature, enabling the pliug to quickly adapt to fit the ear canal. Supplied with a glued plastic band and a practical and hygienic plastic storage case.

- Moulded reusable earplug in TPE-material, fully silicone-free.
- Pliable fins for easy-cleaning.
- Universal size to fit most ear canals.
- Stiff shaft and soft, pliable fins for easy fitting.
- Soft, pliable material for comfortable use.
- Glued retaining plastic band.
- Plastic case for hygienic storage.

Frequency H	łz	63 1	25 250	500	1000	2000	4000	8000
Mean value	(dB)	26,6 2	6,9 24,3	26,1	28,8	32,8	32,6	38,1
Standard de	viation (dB)	6,1 6	,1 4,1	5,1	5,1	5,0	6,5	5,3
Anticipated a	attenuation (dB)	20,5 2	0,8 20,2	21,0	23,7	27,8	26,1	32,8
Н	М	L			SNR			
27	24	2	2		27			
Code	Description			Colou	ır	Uni t	Contents	Pac k
38068805 1	922 L in plastic storag case)	e case (1 pair/	Red	w dark gre retaine		BO X	1	50*







### Reusable earplugs ZEKLER 901

Lightweight earplug where the strap is worn under the chin. The oval earplug fits the ear canal opening and provides a comfortable level of protection which sits properly in position. The fixed position in combination with the ergonomically designed strap minimises scraping sounds from contact with clothing.

#### Complies with EN 352.

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Mean attenuation (dB)	23,7	22	21,6	19	23,8	31,9	39,6	39,6
Standard deviation (dB)	4	2,9	4,7	4,3	3,6	4	2,7	3,7
Assumed protection (dB)	19,7	19,1	16,9	14,7	20,2	27,9	36,9	35,9

 H
 M
 L
 SNR

 27
 19
 18
 24

Code	Description	Туре	Unit	Pack
380688060	Earplug	901		15*
380688061	Spare pods	901		12*







### Reusable earplugs ZEKLER 901

Lightweight earplug where the strap is worn under the chin. The oval earplug fits the ear canal opening and provides a comfortable level of protection which sits properly in position. The fixed position in combination with the ergonomically designed strap minimises scraping sounds from contact with clothing.

#### Complies with EN 352.

Frequency Hz	63	125	250	500	1000	2000	4000	8000
Mean attenuation (dB)	23,7	22	21,6	19	23,8	31,9	39,6	39,6
Standard deviation (dB)	4	2,9	4,7	4,3	3,6	4	2,7	3,7
Assumed protection (dB)	19,7	19,1	16,9	14,7	20,2	27,9	36,9	35,9

 H
 M
 L
 SNR

 27
 19
 18
 24

Code	Description	Туре	Unit	Pack
380688060	Earplug	901		15*
380688061	Spare pods	901		12*